# REMOTE-CONTROLLED **BEAM** SEARCHLIGHTS

### **DETECT • DETER • DISRUPT** HIGH INTENSITY SEARCHLIGHTS FOR SURVEILLANCE, SECURITY AND WEAPON SYSTEMS

Maxa Beam Remote-Controlled Searchlights feature an unparalleled output of 12,000,000 CandlePower and a 6,925 meter range. Searchlights offer visible and IR illumination with a wide variety of remote-controllable features such as beam width, strobe rate, zoom rate, and beam intensity.

The Maxa Beam's powerful output, highly focusable beam and strobe mode enable the searchlight to perform critical roles within the Escalation of Force (EoF) spectrum:

- Long Range Detection and Identification
- Explicit Warning and Deterrence
- Ocular Disruption and Distraction

The Maxa Beam's non-lethal weapon effects are scalable and adaptable to a variety of missions including maritime security, facility/infrastructure security, entry control points, crowd management and border security.







**Peak Beam Systems, Inc.** is a leader in the design and manufacture of high-intensity searchlights for military, defense and security applications. Peak Beam's Maxa Beam Searchlights have been fielded worldwide by military and law enforcement since 1987. Peak Beam Systems is a woman-owned small business based in Newtown Square, Pennsylvania.

# REMOTE-CONTROLLED **BEAM** SEARCHLIGHTS



#### **Quick-Mount Searchlights - MBS-430-Y Series**

Well-suited for surveillance, security and vehicle-mounted applications. Features include 12,000,000 CandlePower output, motorized beam width and user-programmable strobe. MBS-430-Y Searchlights mount using Peak Beam's proprietary four-point locking mechanism for quick attachment with no tools required.



#### Rail-Mounted Searchlights - MBS-430-W4 Series

Well-suited for installation on vehicles, remote weapons stations (RWS), and heavy weapons. Features include 12,000,000 CandlePower output, motorized beam width, and user-programmable strobe. MBS-430-W4 Searchlights mount to any MIL-STD-1913 Picatinny rail with no tools required.




#### **Environmental Enclosure Searchlights - MBPKG-E Series**

Designed for continuous exposure to harsh weather conditions, these 12,000,000 CandlePower searchlights are housed in a marine-grade aluminum enclosure with an internal cooling system for optimum performance in extreme temperatures. Searchlights can be fix-mounted on a variety of platforms including ships and perimeter towers. MBPKG-E Searchlights are controlled with a computer and are often employed with third-party Ethernet-to-serial servers, allowing multiple searchlights to be linked together on the same network.

<u> </u>			www.t.Valte		Compostor Stude			Control Method		Lens Style		Ingress Protection		Features		
L		Input Voltage			Connector Style											
		10VDC- 13.5VDC	18VDC- 36VDC	37VDC- 75VDC	Dual Plastic	Dual Metal	Single Metal	Wired Remote	RS-232 Serial	Standard Spyder Lens	Anodized Aluminum	per CEI/IEC 60529:2001		Motorized Beam Width		Strobe
												IP66	IP67	1° Spot to	1° Spot to	1-31Hz
		1010100			. laotio	motur	metar	Switches	Interface	opyder zene	Lens	11 00	1107	40° Flood	25° Flood	3-63%
QUICK-MOUNT	MBS-430-Y	•			•			•		•		•		•		•
	MBS-430-MY	•				•		•		•			•	•		•
	MBS-430-MM	•				•		•			•		•	•		•
	MBS-430-RSY	•			•			•	•	•		•		•		•
	MBS-430-RSMY	•				•		•	•	•			•	•		•
	MBS-430-RSMM	•				•		•	•		•		•	•		•
RAIL-MOUNT	MBS-430-W4-P	•			•			•		•		•		•		•
	MBS-430-W4	•				•		•		•			•	•		•
	MBS-430-W4-M	•				•		•			•		•		•	•
	MBS-430-W4-RSP	•			•			•	•	•		•		•		•
	MBS-430-W4-RS	•				•		•	•	•			•	•		•
	MBS-430-W4-RSM	•				•		•	•		•		•		•	•
ENCLOSURE	MBPKG-E	•					•	•	•				•	•		•
	MBPKG-E2	•				•		•	•				•	•		•
	MBPKG-E-24		•				•	•	•				•	•		•
	MBPKG-E2-24		•	•		•		•	•				•	•		•
	MBPKG-E-48			•			•		•				•	•		•
_																

For additional information including 3D models, specifications, pin-outs and ASCII computer commands, please contact us at sales@peakbeam.com.





Peak Beam Systems, Inc. 3938 Miller Rd., Newtown Square, PA 19073 Phone: 610-353-8505 • Fax: 610-353-8411 www.peakbeam.com • sales@peakbeam.com Maximum Range: 6,925m (0.25 lux) per ANSI/NEMA FL1: Flashlight Basic Performance Standard

> **Proudly made in the USA.** Copyright © 2024 Peak Beam Systems, Inc.